

ANALYSIS CERTIFICATE / CERTIFICATE OF QUANTITY & QUALITY / MANUFACTURER CERTIFICATE OF PRODUCTION STATING STANDARDS ADOPTED / CERTIFICATE OF ANALYSIS / TEST REPORT / PRODUCTION CERTIFICATE / TEST CERTIFICATE / MANUFACTURERS CERTIFICATE OF PRODUCTION / ANALYSIS REPORT / CHEMICAL ANALYSIS REPORT

Product : POWEROIL PETROLEUM JELLY – EP	
Grade : WHITE SOFT PARAFFIN – EP	
Customer : M/S OLEOHEMIJA d.o.o. Beograd SERBIA. CROATIA	
Mfg Licence No : KD 536 dt.1/11/2003	PO NO. & date : PI APAR-QOT-38493 Dt.22.05.2025
Batch No. : REPW274F25	Quantity : 14.615 MT (79 x 185 Kgs.)
Lab Sr. No. : J-278	Date : 23.06.2025
Mfg. Dt. : JUNE 2025	*Exp. Dt.: MAY 2027
Container No.: MSMU7042642	

Sr. No.	CHARACTERISTICS	TEST METHOD	SPECIFICATION	TEST VALUES
1.	CHARACTERS			
1a.	Appearance	EP	White or almost white, translucent , soft unctuous mass, slightly fluorescent in daylight, when melted.	White , translucent , soft unctuous mass, slightly fluoresent in daylight, when melted.
1b.	Solubility	EP	Practically insoluble in water, Slightly Soluble in methylene chloride, practically insoluble in ethanol (96%) & in glycerol.	Insoluble in water, Slightly Soluble in methylene chloride, practically insoluble in ethanol (96%) & in glycerol.
2.	IDENTIFICATION			
2a.	First Identification A,B, D	EP	Complies with BP monograph	Complies
2b.	Second Identification A, C, D	EP	Complies with BP monograph	Complies
	A. Drop Point, °C	EP	35 - 70	53.0
	D. Appearance	EP	Melted mass is not intensely coloured than standard mixture	Complies
3.	TESTS			
3a.	Appearance	EP	Melted mass is not intensely coloured than standard mixture	Complies
3b.	Acidity or Alkalinity	EP	Not more than 0.5 ml of 0.01 M NaoH	Complies
3c.	Consistency	EP	60 to 300	168
3d.	Polycyclic Aromatic Hydrocarbons	EP	Should Pass	Complies
3e.	Sulphated Ash	EP	0.05 % , Max.	Nil
4.	Additional Tests Parameters			
4a.	Density at 60°C, g/cm ³	ASTM D 1298	-	0.833
4b.	Kinematic Viscosity at 70°C,cSt	ASTM D 445	-	12.64
4c.	Kinematic Viscosity at 100°C,cSt	ASTM D 445	-	6.496

Remarks : Conforms to EP 11 specification for White Soft Paraffin.

* Subject to product being stored in cool place and protected from light & moisture.



ANALYSIS CERTIFICATE / CERTIFICATE OF QUANTITY & QUALITY / MANUFACTURER CERTIFICATE OF PRODUCTION STATING STANDARDS ADOPTED / CERTIFICATE OF ANALYSIS / TEST REPORT / PRODUCTION CERTIFICATE / TEST CERTIFICATE / MANUFACTURERS CERTIFICATE OF PRODUCTION / ANALYSIS REPORT / CHEMICAL ANALYSIS REPORT

Product : POWEROIL PETROLEUM JELLY – EP	
Grade : WHITE SOFT PARAFFIN – EP	
Customer : M/S OLEOHEMIJA d.o.o. Beograd SERBIA. CROATIA	
Mfg Licence No : KD 536 dt.1/11/2003	PO NO. & date : PI APAR-QOT-38493 Dt.22.05.2025
Batch No. : REPW273F25	Quantity : 0.185 MT (1 x 185 Kgs.)
Lab Sr. No. : J-277	Date : 23-06-2025
Mfg. Dt. : JUNE 2025	*Exp. Dt.: MAY 2027
Container No.: MSMU7042642	

Sr. No.	CHARACTERISTICS	TEST METHOD	SPECIFICATION	TEST VALUES
1.	CHARACTERS			
1a.	Appearance	EP	White or almost white, translucent , soft unctuous mass, slightly fluorescent in daylight, when melted.	White , translucent , soft unctuous mass, slightly fluorescent in daylight, when melted.
1b.	Solubility	EP	Practically insoluble in water, Slightly Soluble in methylene chloride, practically insoluble in ethanol (96%) & in glycerol.	Insoluble in water, Slightly Soluble in methylene chloride, practically insoluble in ethanol (96%) & in glycerol.
2.	IDENTIFICATION			
2a.	First Identification A,B, D	EP	Complies with BP monograph	Complies
2b.	Second Identification A, C, D	EP	Complies with BP monograph	Complies
	A. Drop Point, °C	EP	35 - 70	52.5
	D. Appearance	EP	Melted mass is not intensely coloured than standard mixture	Complies
3.	TESTS			
3a.	Appearance	EP	Melted mass is not intensely coloured than standard mixture	Complies
3b.	Acidity or Alkalinity	EP	Not more than 0.5 ml of 0.01 M NaoH	Complies
3c.	Consistency	EP	60 to 300	170
3d.	Polycyclic Aromatic Hydrocarbons	EP	Should Pass	Complies
3e.	Sulphated Ash	EP	0.05 % , Max.	Nil
4.	Additional Tests Parameters			
4a.	Density at 60°C, g/cm ³	ASTM D 1298	-	0.833
4b.	Kinematic Viscosity at 70°C,cSt	ASTM D 445	-	12.82
4c.	Kinematic Viscosity at 100°C,cSt	ASTM D 445	-	6.584

Remarks : Conforms to EP 11 specification for White Soft Paraffin.

* Subject to product being stored in cool place and protected from light & moisture.

